






FLEXIBLE

Star
ABRASIVES

Technical Specifications

Type	A35	A36	A39
Grit Range & Grain	P120-P800: Silicon Carbide	P80-P600: Semi-friable Aluminum Oxide	P80-P800: Premium Brown Aluminum Oxide
Backing	Awt high latex content paper	Latex-reinforced Cwt paper	Fiber-reinforced Cwt paper
Bonding	Resin/Resin	Resin/Resin	Resin/Resin
Coating	Semi-open coating	Open coating	Open coating
Anti-clogging Layer	Stearate	Special anti-clogging layer	Stearate

Type	Features	Benefits
 A35	<ul style="list-style-type: none"> • Awt High Latex content Paper • Silicon carbide grain • Resin/resin bonding system • Stearate coating layer 	<ul style="list-style-type: none"> • Highly flexible and comfortable for manual operation • Better surface quality • Fine stock removal • Good anti-clogging performance on painting & putty
 A36	<ul style="list-style-type: none"> • Premium semi-friable aluminum oxide grain • Unique Cwt latex reinforced paper backing • Additional coating layer 	<ul style="list-style-type: none"> • Faster cut rate, superior service life • More flexible can be folded without cracking • Good Anti-clogging performance on painting & putty
 A39	<ul style="list-style-type: none"> • Premium heated aluminum oxide • Fiber-reinforced backing paper • Resin/resin bonding system • Additional coating layer and open coat 	<ul style="list-style-type: none"> • Faster cut and longer service life, more durable • Better grain retention and tear-resistance, highly flexible for easy folding and unfolding • Fine stock removal • Anti-clogging, resistance to clogging and loading during sanding

Type	Applications	Forms
A35	<ul style="list-style-type: none"> Primary paint grinding Wood and synthetic material grinding and polishing Wood veneer sanding 	
A36	<ul style="list-style-type: none"> Automotive painting and refinishing Sanding out unevenness at the edges of repaired surface Flatting of body filler and primer filler 	
A39	<ul style="list-style-type: none"> Removal of wood, paint, varnish or rust Final sanding of surfaces prior to coating with stain, primer or sealer Light sanding or cleaning of surface 	